

VISU-LINK MPVL-6



FEATURES:

- Environmentally sealed
- Connects to Meter M.I.U.
- Large easy to read display
- “TAP” switch to get current meter reading.
- Rugged, durable construction.

PHYSICALS:

- 5” Diameter X 1½”
- 10 feet CAT 5 cable standard, request more if needed.

METER CONNECTIVITY:

- Sensus
- Invensys
- Neptune
- Schlumberger
- Operating Temperature:
-20 to 60°C (-4 to 140°F)

INSTALLATION:

The Visu-Link module has a mounting flange around the base of the unit with four pre-drilled holes for mounting. Use appropriate mounting hardware (screws, etc.) depending on your application (wood, masonry, etc.)

-Use appropriate safety equipment.

-Mount the Visu-Link right side up (the program read coil is on top and the MIU cable is located on the bottom).

-Connect the MIU cable to the meter with the following chart:

Visu-Link Sensus/ Neptune/

Module Invensys Schlumberger

RED-----RED-----BLACK

GREEN-----GREEN-----RED

BLACK-----BLACK-----GREEN

-Terminate wire connections with appropriate wire connectors. We recommend insulation displacement connectors. They provide a insulative and waterproof

barrier for the spliced connection.-Confirm installation by activating the module (activate module by tapping on "TAP" switch for visual confirmation).

-Secure all connections.

-Clean up area and tools.

-Safety is your responsibility.